

## Valena™ television sockets









7 743 29 + 7 700 21

7 744 32 + 7 744 51

7 701 36 + 7 703 91

7 743 42

Mechanisms supplied with cover plates, to be equipped with plates (p. 498-499) Screw or claw mounting

Pack	Cat.Nos	Single TV sockets
		For plugs with Ø9.5 mm TV male: 4 to 2400 MHz
		Star socket
10	7 743 29	Attenuation ≤ 1.5 dB
10	7 744 29	○ White
10	7 701 29	Brilliant Aluminium
		Terminal socket
10	7 740 00	Attenuation ≤ 10 dB
10	7 743 30 7 744 30	Ivory   White
10	7 701 30	Brilliant Aluminium
		Throughwiring socket
40	7 740 04	Attenuation ≤ 14 dB
10 10	7 743 31 7 744 31	Ivory   White
10	7 701 31	Brilliant Aluminium

		TV-R sockets		
		For plugs with Ø9.5 mm TV male: 4 to 862 MHz R female: 87.5 to 108 MHz		
		Star socket		
		Attenuation ≤ 1.5 dB		
10	7 743 32	● Ivory		
10	7 744 32	₩ O White		
10	7 701 32	Brilliant Aluminium		
		<b>Terminal socket</b> Attenuation ≤ 10 dB		
10	7 743 33	○ Ivory		
10	7 744 33	₩hite		
10	7 701 33	Brilliant Aluminium		
		Throughwiring socket		
		Attenuation ≤ 14 dB		
10	7 743 34	Attenuation ≤ 14 dB  Nory		
10 10	7 743 34 7 744 34			
		● Ivory		

Pack	Cat.Nos	TV-R-SAT sockets	
		For plugs with Ø9.5 mm Equipped with connectors for automatic connection (no need to strip conductive cable) TV male - 4 to 862 MHz R female 87.5 to 108 MHz SAT (IF + IF 2) 950 to 2400 MHz	
		Star socket	
		Attenuation ≤ 1.5 dB	
10 10	7 743 35 7 744 35	○ Ivory ○ White	
10	7 701 35	White     Brilliant Aluminium	
	7 701 00	Terminal socket	
		Attenuation ≤ 10 dB	
10	7 743 36	Attendation 5 10 db	
10	7 744 36	White	
10	7 701 36	Brilliant Aluminium	
	Throughwiring socket		
		Attenuation ≤ 14 dB	
10	7 743 37	○ Ivory	
10 10	7 744 37	White Prillipst Aluminium	
10	7 701 37	Brilliant Aluminium	

		T
10	7 743 42	3 to a
10	7 743 42 7 744 42	9
10	7 701 42	Į

## TV-R central plates

30 mm with screw for adaptation to local manufacturers such as DX Contera, Televes and Hirschmann

O Ivory



O White

Brilliant Aluminium